

**▼ FULL BLACK** 

Mono Shingled Solar Panels



## **BSM70PM5-S**

## **Warranty**

5 years Manufacturer Warranty Warranty on Electrical Performance: 10 years 90% + 25 years 80% of power output

## **Manufacturing**

Original cell sorting system ensures the best electric cell match EL-Testing before packing. Comprehensive module power testing.

## **Performance**

Higherer module efficiency and compact size Weakened hot-spot effect, lower module failure rate and increased stability by shingle-tech. Special connection method lowers the internal resistance and ensures better performance than traditional connection with busbar. IP67 rated junction box, reliable cables and standard MC4 connectors improve the stability

Mechanical Data Standard Test Conditions AM=1.5, E=1000W/m2, TC=25°C	
Nominal Power	70W
Cell Type	Monocrystalline
Cell Efficiency	21.1%
Maximum Power Current (Impp)	3.01A
Maximum Power Voltage (Vmpp)	23.25V
Open-circuit Voltage (Voc)	27.64V
Short-circuit Current (Isc)	3.19A
Maximum System Voltage	500V
Output Tolerance	+3%
Cable	500mm / 2.5mm <sup>2</sup>
Connector Type	MC4 / MC4 Compatible
Module Structure	Aluminum Frame / Glass / EVA / Backsheet (White)
Junction box rating	≥IP67
Number of Diodes	One
Working Temperature	-40°C∼+80°C
Packaging	
Module Dimensions	1050*350*30mm
Module Weight	4.2kg
Package	Single Package
Pieces per Pallet	100
Gross Weight per Pallet	440kg
Pallet Dimensions	1300*1150*1250mm



